

In terms of section 75 of the Customs and Excise Act, 1964, Part 2 of Schedule No. 4 to the said Act is hereby amended to the extent set out in the Schedule hereto.

M GUNGUBELE
DEPUTY MINISTER OF FINANCE

SCHEDULE

By the insertion of the following:

Rebate Item	Tariff Heading	Rebate Code	CD	Description	Extent of Rebate
460.15	7208.5	04.05	53	Flat-rolled products of iron or non-alloy steel, of a width of 600 mm or more, not in coils, not further worked than hot-rolled, of a thickness of 2 mm or more but not exceeding 160 mm, with a yield strength of 550 MPa or more but not exceeding 960 MPa and having an impact strength of 27 Joules or more but not exceeding 69 Joules at -20°C or less but not less than -60°C, at such times, in such quantities and subject to such conditions as the International Trade Administration Commission may allow by specific permit, provided the products are not available in the SACU market	Full duty in Schedule No. 1 and Schedule No. 2
460.15	7208.5	05.05	58	Flat-rolled products of iron or non-alloy steel, of a width of 600 mm or more, not in coils, not further worked than hot-rolled, of a thickness of 2 mm or more but not exceeding 160 mm, with a Brinell hardness of 400 HBW or more but not exceeding 700 HBW and having an impact strength of 15 Joules or more but not exceeding 95 Joules at -40°C, at such times, in such quantities and subject to such conditions as the International Trade Administration Commission may allow by specific permit, provided the products are not available in the SACU market	Full duty in Schedule No. 1 and Schedule No. 2
460.15	7208.5	06.05	52	Flat-rolled products of iron or non-alloy steel, of a width of 600 mm or more, not in coils, not further worked than hot-rolled, of a thickness of 40 mm or more but not exceeding 160 mm, with a Brinell hardness of 350 HBW and having an impact strength of 95 Joules at -40°C, at such times, in such quantities and subject to such conditions as the International Trade Administration Commission may allow by specific permit, provided the products are not available in the SACU market	Full duty in Schedule No. 1 and Schedule No. 2
460.15	7208.5	07.05	57	Flat-rolled products of iron or non-alloy steel, of a width of 600 mm or more, not in coils, not further worked than hot-rolled, of a thickness of 5 mm or more but not exceeding 50 mm, with a Brinell hardness of 350 HBW and having an impact strength of 60 Joules at -40°C, at such times, in such quantities and subject to such conditions as the International Trade Administration Commission may allow by specific permit, provided the products are not available in the SACU market	Full duty in Schedule No. 1 and Schedule No. 2
460.15	7225.40	04.06	61	Flat-rolled products of other alloy steel, of a width of 600 mm or more, not further worked than hot-rolled, not in coils, of a thickness of 2 mm or more but not exceeding 160 mm, with a yield strength of 550 MPa or more but not exceeding 960 MPa and having an impact strength of 27 Joules or more but not exceeding 69 Joules at -20°C or less but not less than -60°C, at such times, in such quantities and subject to such conditions as the International Trade Administration Commission may allow by specific permit, provided the products are not available in the SACU market	Full duty in Schedule No. 1 and Schedule No. 2
460.15	7225.40	05.06	66	Flat-rolled products of other alloy steel, of a width of 600 mm or more, not further worked than hot-rolled, not in coils, of a thickness of 2 mm or more but not exceeding 160 mm, with a Brinell hardness of 400 HBW or more but not exceeding 700 HBW and having an impact strength of 15 Joules or more but not exceeding 95 Joules at -40°C, at such times, in such quantities and subject to such conditions as the International Trade Administration Commission may allow by specific permit, provided the products are not available in the SACU market	Full duty in Schedule No. 1 and Schedule No. 2

By the insertion of the following:

Rebate Item	Tariff Heading	Rebate Code	CD	Description	Extent of Rebate
460.15	7225.40	06.06	60	Flat-rolled products of other alloy steel, of a width of 600 mm or more, not further worked than hot-rolled, not in coils, of a thickness of 40 mm or more but not exceeding 160 mm, with a Brinell hardness of 350 HBW and having an impact strength of 95 Joules at -40°C, at such times, in such quantities and subject to such conditions as the International Trade Administration Commission may allow by specific permit, provided the products are not available in the SACU market	Full duty in Schedule No. 1 and Schedule No. 2
460.15	7225.40	07.06	65	Flat-rolled products of other alloy steel, of a width of 600 mm or more, not further worked than hot-rolled, not in coils, of a thickness of 5 mm or more but not exceeding 50 mm, with a Brinell hardness of 350 HBW and having an impact strength of 60 Joules at -40°C, at such times, in such quantities and subject to such conditions as the International Trade Administration Commission may allow by specific permit, provided the products are not available in the SACU market	Full duty in Schedule No. 1 and Schedule No. 2
460.15	7225.40	08.06	63	Flat-rolled products of other alloy steel, of a width of 600 mm or more, not further worked than hot-rolled, not in coils, of a thickness of 2 mm or more but not exceeding 100 mm, with a nickel content of 1.8 per cent by mass or more but not exceeding 3 per cent, a molybdenum content of 0.7 per cent by mass or more but not exceeding 0.8 per cent and a chrome content of 1 per cent by mass or more but not exceeding 2 per cent, with a Brinell hardness of 260 HBW or more but not exceeding 640 HBW, at such times, in such quantities and subject to such conditions as the International Trade Administration Commission may allow by specific permit, provided the products are not available in the SACU market	Full duty in Schedule No. 1 and Schedule No. 2
460.15	7225.40	09.06	64	Flat-rolled products of other alloy, of a width of 600 mm or more, not further worked than hot-rolled, not in coils, with a thickness of 2 mm or more but not exceeding 20 mm, with a copper content of 0.25 per cent by mass or more but not exceeding 0.4 per cent and a chromium content of 1 per cent by mass or more but not exceeding 2 per cent, with a yield strength of 550 MPa or more but not exceeding 960 MPa, at such times, in such quantities and subject to such conditions as the International Trade Administration Commission may allow by specific permit, provided the products are not available in the SACU market	Full duty in Schedule No. 1 and Schedule No. 2